### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

. Tebbe reagent solution

#### ProductName 2. HAZARDS IDENTIFICATION

Risk advice to man and the environment

Highly flammable. Causes burns. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms Bis(cyclopentadienyl)-  $\mu$  -chloro(dimethylaluminum)-  $\mu$  methylenetitanium

Formula C13H18AlClTi

CAS-No. EC-No. Classification Concentration Tolue ne >= 85 % 108-88-3 203-625-9 F, Xn, Repr.Cat.3, R11 -

R38 - R48/20 - R63 - R65 -

 $\mu$  -Chlorobis (  $\eta$  5-2,4-cyclope ntadie n-1-yl)(dimethylaluminum)-  $\mu$  -methyle ne-titanium C, R34

>= 10 - <= 15 %

4. FIRST AID MEASURES

For the full text of the R-phrases mentioned in this Section, see Section 16.

#### General advice Consult a physician. Show this safety data sheet to the doctor in attendance.

If breathed in, move person into fresh air. If not breathing give artificial respiration Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a

In case of skin contact

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIRE-FIGHTING MEASURES

physician.

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

## Special protective equipment for fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary. Further information Use water spray to cool unopened containers.

## concentrations. Vapours can accumulate in low areas.

Methods for cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous

earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Handling Avoid inhalation of vapour or mist.

#### Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

## Storage

opened must be carefully resealed and kept upright to prevent leakage.

Air sensitive. Moisture sensitive.

Respiratory protection Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering

# Hand protection

Eye protection Tightly fitting safety goggles. Faceshield (8-inch minimum). Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at

# **Appe arance**

Ignition temperature

Safety data рΗ no data available

#### Melting point no data available Boiling point no data available

9. PHYSICAL AND CHEMICAL PROPERTIES

# Flash point

place.

Lower explosion limit no data available Upper explosion limit 0,960 g/cm3 Density Water solubility no data available 10. STABILITY AND REACTIVITY Storage stability Stable under recommended storage conditions. Conditions to avoid Heat, flames and sparks. Materials to avoid Strong oxidizing agents

# Titanium/titanium oxides, Aluminum oxide 11. TOXICOLOGICAL INFORMATION

Hazardous decomposition products

Sensitisation no data available Chronic exposure

Lung irritation, chest pain, pulmonary edema, Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals.

Harmful if inhaled. Material is extremely destructive to the tissue of the mucous

membranes and upper respiratory tract. Vapours may cause drowsiness and

May be harmful if absorbed through skin. Causes skin burns.

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Hydrogen chloride gas,

# IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Toluene)

Causes eye burns. Ingestion May be harmful if swallowed. Causes burns. Aspiration hazard if swallowed - can enter lungs and cause damage. **Target Organs** Bladder, Liver, Kidney, Brain.,

### no data available **Ecotoxicity effects** no data available

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

professional waste disposal service to dispose of this material.

13. DISPOSAL CONSIDERATIONS

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations. Contact a licensed

Packing group: II

Packing group: II

Packing group: II

EMS-No: F-E, S-C

UN-Number: 2924 Class: 3 (8) Proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (μ-Chlorobis(η 5-2,4-cyclopentadien-1yl)(dimethylaluminum)- μ -methylene-titanium, Toluene) **IMDG** UN-Number: 2924 Class: 3 (8) Proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. ( μ -Chlorobis( η 5-2,4-cyclopentadien-1-

ADR/RID

Contaminated packaging Dispose of as unused product.

14. TRANSPORT INFORMATION

Labelling according to EC Directives

Keep away from sources of ignition - No smoking.

Proper shipping name: Flammable liquid, corrosive n.o.s. (μ -Chlorobis(η 5-2,4-cyclopentadien-1-

R-phrase(s) R11

R65 R67 S-phrase(s)

S16

Hazardous components which must be listed on the label: 108-88-3 Toluene  $\mu$  -Chlorobis(  $\eta$  5-2,4-cyclopentadien-1-yl)(dimethylaluminum)-  $\mu$  -methylene-titanium

Text of R-phrases mentioned in Section 3 R11 Highly flammable.

R34 Causes burns. Irritating to skin.

R38 R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R63 Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. R65 R67 Vapours may cause drowsiness and dizziness. Further information

www.lookchem.com

For R&D use only. Not for drug, household or other uses. WARRANTY: The above information is believed to be correct but does not purport to be all inclusive and shall be used

only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Lookchem shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Suitable extinguishing media

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

7. HANDLING AND STORAGE

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are

8. EXPOSURE CONTROLS/PERSONAL PROTECTION Personal protective equipment

controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. Handle with gloves.

Hygiene measures the end of workday.

liquid Form

4 °C - closed cup

no data available

no data available

### Acute toxicity no data available Irritation and corrosion

Signs and Symptoms of Exposure

no data available

Skin Eves

Inhalation

**Potential Health Effects** 

Further information on ecology no data available

yl)(dimethylaluminum)- μ -methylene-titanium, Toluene)

Marine pollutant: No

UN-Number: 2924 Class: 3 (8)

15. REGULATORY INFORMATION

**IATA** 

Hazard symbols C

R34 R48/20

R63 Vapours may cause drowsiness and dizziness.

67719-69-1

S45 label where possible). S62 container or label.

S36/37/39 In case of accident or if you feel unwell, seek medical advice immediately (show the If swallowed, do not induce vomiting: seek medical advice immediately and show this

16. OTHER INFORMATION

Corrosive Highly flammable. Causes burns. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.

Highly flammable

yl)(dimethylaluminum)- μ -methylene-titanium, Toluene)

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical Wear suitable protective clothing, gloves and eye/face protection.