# CoorsTek MATERIAL SAFETY DATA SHEET

CoorsTek, 600 Ninth Street, Golden, Colorado 80401	EMERGENCY TELI (303) 278-4000	EPHONE NO:	
TRADE NAME:	MSDS NUMBER:		DATE OF ISSUE:
Alumina-Silicate	09		01/01/00
CHEMICAL NAME:	SYNONYMS:		
Sintered Non-Porous Alumina Silicate	C-1; C-2; C-3; C-4;		
PREPARED BY:	REVISION:	REVISION DATE:	DATE OF REVIEW:
Environmental, Health and Safety	02	01/01/00	01/01/00

## **1. INGREDIENTS**

MATERIAL	PERCENT	ACGIH (TLV)	OSHA (PEL)
1. Aluminum Oxide (CAS # 1344-28-1)	< 45	10 mg/m <sup>3</sup> (T)	5 mg/m <sup>3</sup> (R) 15 mg/m <sup>3</sup> (T)
2. Potassium Oxide (CAS # 12136-45-7)	< 3	Not Established	Not Established
3. Titanium Oxide (CAS # 13463-67-7)	< 2	10 mg/m <sup>3</sup> (T)	15 mg/m <sup>3</sup> (T)
4. Amorphous Phase (See Comment 1., Section 11.)	< 56	Not Established	Not Established
All values are Time-Weighted Averages T = Total Particulate Matter R = Respirable Fraction of Particulate Matter			

## 2. PHYSICAL DATA

	=		
APPEARANCE:	ODOR:	MELTING POINT:	SPECIFIC GRAVITY:
White Inert Solid	Odorless	$> 1450^{\circ}C / > 2640^{\circ}F$	2.37 minimum
VAPOR DENSITY (AIR = 1):	% VOLATILE BY VOLUME:	BULK DENSITY:	BOILING POINT:
NA	NA	NA	NA
VAPOR PRESSURE:	% SOLUBILITY (H <sub>2</sub> O):	EVAPORATION RATE (BuOAC = 1):	OTHER:
NA	Negligible	NAIF	NAIF

# 3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT & METHOD:	
NA	
FLAMMABLE LIMITS	
LEL: NA	UEL: NA
EXTINGUISHING MEDIA:	
Will not burn. Select media which is appropriate for fighting	ng surrounding fire.
SPECIAL FIRE-FIGHTING PROCEDURES:	
fighting	with full face piece operated in pressure demand or other positive pressure mode. Wear full fire-
protective clothing.	
protective clothing.	
UNUSUAL FIRE AND EXPLOSION HAZARDS	
Not an explosion hazard.	

### 4. HEALTH HAZARD DATA

LD50 ORAL (INGESTION) NAIF	LD50 DERMAL (SKIN CONTACT) NAIF	LD50 (INHALATION) NAIF
PRIMARY ROUTE OF EXPOSURE Inhalation		
EFFECTS OF OVEREXPOSURE: FIRED OR SINT	ERED MATERIAL HAS NO KNOWN HEALTH F	IAZARDS.
ACUTE: High dust concentrations may cause mechanica	al eye irritation and upper respiratory irritation. Pro	longed skin contact with powder may cause drying.
CHRONIC: Chronic exposure to dusts may cause pneum	oconiosis.	
There are no known medical conditions aggra	avated by exposure to this product.	

### 5. EMERGENCY AND FIRST AID PROCEDURES

Inhalation: Move to area free from risk of further exposure. Administer oxygen or artificial respiration, as needed. Get medical attention.

Eye Contact: Flush with tepid water for at least 15 minutes while holding eyelids open. Seek medical attention if irritation develops.

Skin Contact: Wash affected areas with soap and water. Seek medical attention if irritation develops.

Ingestion: Not a likely route of exposure. If large amounts of product are ingested, give two glasses of water and get prompt medical attention. Never give anything by mouth to an unconscious person.

## 6. PHYSICAL HAZARDS

None known.

### 7. SPECIAL PROTECTION INFORMATION

#### VENTILATION:

If dust is generated during processing or use, local exhaust should be provided to maintain exposures below the limits cited in Section 1. Design details for local exhaust ventilation systems may be found in the latest edition of "Industrial Ventilation: A Manual of Recommended Practices" published by ACGIH Committee on Industrial Ventilation, PO Box 16153, Lansing, MI 48910. The need for local exhaust ventilation should be evaluated by a professional industrial hygienist. Local Exhaust systems should be designed by a professional engineer.

RESPIRATORY:

If airborne concentrations may exceed the exposure limits outlined in Section 1, use a NIOSH/MSHA approved respirator for dusts and mists with an exposure limit of not less than  $0.05 \text{ mg/M}^3$ . If exposures exceed 10 times the recommended limits, consult a professional industrial hygienist, or your respiratory equipment supplier, about the selection of the proper equipment. The evaluation of the need for respiratory protection should be determined by a professional industrial hygienist.

EYE PROTECTION: Safety glasses are recommended.

#### PROTECTIVE GLOVES:

Wear any polymer gloves if prolonged exposure to powder is expected.

ALL CHEMICALS SHOULD BE HANDLED SO AS TO PREVENT EYE CONTACT AND EXCESSIVE OR REPEATED SKIN CONTACT. APPROPRIATE EYE AND SKIN PROTECTION SHOULD BE EMPLOYED. INHALATION OF DUSTS AND VAPORS SHOULD BE AVOIDED.

#### 8. CHEMICAL REACTIVITY

CONDITIONS CAUSING INSTABILITY: Stable. None known.

INCOMPATIBILITY (MATERIALS TO AVOID): None known.

#### HAZARDOUS DECOMPOSITION PRODUCTS:

May include oxides of aluminum, titanium or potassium at high temperatures.

SPECIAL SENSITIVITY: None known.

#### 9. STORAGE INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool, dry area. Any dust generated during handling or processing should be removed by wet mopping or vacuuming. Avoid breathing dusts.

## **10. SPILL, LEAK, AND DISPOSAL INFORMATION**

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Secure area and obtain necessary personal protective equipment. Scoop up material and place in appropriate containers for reuse or disposal. Do not allow material to enter sewer or waterways. Small amounts may be cleaned up by wet mopping or vacuuming.

EPA RCRA ID NUMBER: NA

#### WASTE DISPOSAL METHOD:

This material, if discarded, is not defined as hazardous under 40 CFR 261. Disposal in a landfill in accordance with applicable federal, state, and local laws or regulations is recommended.

PAGE 3 OF 4 / MSDS 09

## **11. ADDITIONAL COMMENTS**

- 1. Amorphous phase is composed of silicon dioxide, aluminum oxide, and magnesium oxide.
- 2. This product contains the following ingredients which are listed as Special Health Hazard Substances by the State of New Jersey: None
- 3. This product contains the following ingredients which are listed as hazardous substances under the State of New Jersey Right-To-Know legislation: None
- 4. This product contains the following ingredients which are listed as Special Hazardous Substances by the Commonwealth of Pennsylvania: None.
- 5. This product contains the following ingredients which are listed as Extraordinarily Hazardous Substances by the Commonwealth of Massachusetts: None
- 6. This product contains the following ingredients listed under Proposition 65 of the State of California: None
- 7. This product contains the following ingredients listed on the Toxic Substances Control Act Chemical Substances Inventory List: Aluminum oxide, silicon dioxide, magnesium oxide, potassium oxide, and titanium oxide.
- 8. Pursuant to Section 313, SARA Title III, this product contains the following reportable substances: None
- 9. OSHA Hazard Communication Categories: Irritant, Eye Hazard, Lung Hazard.
- 10. SARA: Fire No; Pressure No; Reactive No; Acute Yes; Chronic Yes.
- 11. No DOT labels are required, no DOT Hazard ID Number has been assigned, and no DOT shipping restrictions apply.
- 12. Judgments as to the suitability of the information herein for purchaser's purposes are necessarily purchaser's responsibility. Therefore, although reasonable care has been taken in the preparation if such information, Coors Ceramics Company extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes or for consequences of its use.

PAGE 4 OF 4 / MSDS 09