

according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: (REACH)

 Date of print:
 09.07.2011

 Revision date:
 30.01.2011

 Date of first version:
 28.07.2010

2,3',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-086S

Version 2 / Page 1 of 9

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name: 2,3',5-Tribromobiphenyl 100 µg/mL in Hexane

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

General use specific analysis

#### 1.3 Details of the supplier of the safety data sheet

| Company name:                   | LGC Standards GmbH   |  |  |
|---------------------------------|----------------------|--|--|
| Street/POB-No.:                 | Mercatorstr. 51      |  |  |
| State/city/postal code:         | D-46485 Wesel        |  |  |
| World Wide Web:                 | www.lgcstandards.com |  |  |
| Email:                          | de@lgcstandards.com  |  |  |
| Telephone:                      | +49 (0)281-98 87-0   |  |  |
| Telefax:                        | +49 (0)281-98 87-199 |  |  |
| Deal second like for hefe works |                      |  |  |

Dept. responsible for information:

Telephone: +49 (0)281-98 87-0, Email: de@lgcstandards.com

#### **1.4 Emergency telephone number**

Telephone: +49 (0)281-98 87-0 Only available during office hours.

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Directive 67/548/EEC or 1999/45/EC

| Repr. Cat. 3; R62 | Possible risk of impaired fertility.  |
|-------------------|---|
| F; R11            | Highly flammable.   |
| Xn; R48/20        | Harmful: danger of serious damage to health by prolonged exposure through inhalation.       |
| Xn; R65           | Harmful: may cause lung damage if swallowed.  |
| Xi; R38           | Irritating to skin.   |
| R67               | Vapours may cause drowsiness and dizziness.   |
| N; R51-53         | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

Xn

#### 2.2 Label elements

#### Labelling (67/548/EEC or 1999/45/EC)



harmful

highly flammable



dangerous for the environment

| R phrase(s): | R 11    | Highly flammable.   |
|--------------|---------|---|
|              | R 38    | Irritating to skin.   |
|              | R 48/20 | Harmful: danger of serious damage to health by prolonged exposure through inhalation.       |
|              | R 51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
|              | R 62    | Possible risk of impaired fertility.  |
|              | R 65    | Harmful: may cause lung damage if swallowed.  |
|              | R 67    | Vapours may cause drowsiness and dizziness.   |



according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: 28.07.2010 (REACH)

2,3',5-Tribromobiphenyl 100 µg/mL in Hexane

| Material | number | U-RBF-086S |
|----------|--------|------------|
|          |        |            |

Version 2 / Page 2 of 9

09.07.2011

Date of print:

| S phrase(s): | S (2)    | Keep out of the reach of children.   |
|--------------|----------|--|
|              | S 9      | Keep container in a well-ventilated place.   |
|              | S 16     | Keep away from sources of ignition - No smoking.                                     |
|              | S 29     | Do not empty into drains.  |
|              | S 33     | Take precautionary measures against static discharge.                                |
|              | S 36/37  | Wear suitable protective clothing and gloves.  |
|              | S 61     | Avoid release to the environment. Refer to special instructions / safety data sheet. |
|              | S 62     | If swallowed, do not induce vomiting: seek medical advice immediately and show       |
|              |          | this container or label.   |
|              | <b>a</b> |  |

Text for labelling Contains n-Hexane.

#### 2.3 Other hazards

No risks worthy of mention.

# **SECTION 3: Composition/ information on ingredients**

3.1 Substances: not applicable

#### 3.2 Mixtures

Hazardous ingredients:

| Ingredient                          | Chemical name | Content   | Classification   |
|-------------------------------------|---------------|-----------|--|
| EINECS -<br>CAS 59080-35-2          | 2,3',5-PBB    | < 0,1 %   | EU: N; R50-53. R33. Xn; R22. Xi; R36/37/38.<br>CLP: Acute Tox. 4; H302. Skin Irrit. 2; H315. Eye Irrit. 2; H319.<br>STOT SE 3; H335. STOT RE 2; H373. Aquatic Acute 1; H400.<br>Aquatic Chronic 1; H410.                             |
| EINECS<br>203-777-6<br>CAS 110-54-3 | n-Hexane      | >= 99,9 % | EU: F; R11. N; R51-53. R67. Repr. Cat. 3; R62. Xi; R38.<br>Xn; R48/20. Xn; R65.<br>CLP: Flam. Liq. 2; H225. Skin Irrit. 2; H315. Repr. 2; H361f.<br>STOT SE 3; H336. STOT RE 2; H373. Asp. Tox. 1; H304.<br>Aquatic Chronic 2; H411. |

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

| After inhalation:        | Move victim to fresh air. If the casualty has difficulty breathing, call a doctor immediately.<br>If breathing becomes irregular or ceases, apply mouth-to-mouth resuscitation or artificial<br>respiration immediately, where required supply oxygen. |
|--------------------------|--|
| In case of skin contact: | Take off immediately all contaminated clothing.<br>After contact with skin, wash immediately with soap and plenty of water.<br>In case of skin irritation, consult a physician.  |
| After eye contact:       | With eyelids open, wash out eyes for several minutes under flowing water. In case of troubles or persistent symptoms, consult an opthalmologist.   |
| After swallowing:        | Rinse mouth thoroughly with water.<br>Caution if victim vomits: Risk of aspiration! Immediately get medical attention.<br>Keep airway open. Give activated carbon (20 - 40 g in a suspension of 10%).<br>Do not give fatty oils and milk.              |
| <b>4.2 Most import</b>   | ant symptoms and officers, both acuto and dolayod  |

#### 4.2 Most important symptoms and effects, both acute and delayed

No data available

#### 4.3 Indication of any immediate medical attention and special treatment needed

No special measures are required.



according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: 2 (REACH)

 Date of print:
 09.07.2011

 Revision date:
 30.01.2011

 Date of first version:
 28.07.2010

### 2,3',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-086S

Version 2 / Page 3 of 9

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media:

Extinguishing powder, foam, carbon dioxide.

In case of greater fires: Foam or water fog.

Extinguishing media which must not be used for safety reasons: High power water jet

#### 5.2 Special hazards arising from the substance or mixture

Highly flammable. Explosive mixtures with air may even form at room temperature. Concentrated vapours are heavier than air. Beware of reignition.

In case of fire may be liberated: Carbon monoxide and carbon dioxide, traces of incompletely burned carbon compounds.

#### **5.3 Advice for firefighters**

Special protective equipment for firefighters:

Wear self-contained breathing apparatus. Wear full protective gear.

Additional information: Cool endangered containers with water spray and, if possible, remove from danger zone. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Contaminated fire-fighting water must be collected separately.

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Plug leak if safely possible. Avoid contact with the substance. Wear suitable protective clothing. Do not breathe vapour/aerosol. Provide adequate ventilation. In case of spills of large quantities: Use appropriate respiratory protection.

#### 6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains. Danger of explosion! In case of release, notify competent authorities.

#### 6.3 Methods and material for containment and cleaning up

Take up with non-flammable, liquid binding material (e.g. sand/earth/diatomaceous earth/vermiculit) and perform disposal according to instructions. Thoroughly clean surrounding area.

In case of spills of large quantities: Dam spills and pump to remove. Contact expert.

Additional information: Beware of reignition. Use only spark proof tools.

#### 6.4 Reference to other sections

not required

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advices on safe handling Provide adequate ventilation, and local exhaust as needed. Execute works under fume hood. Provide room air exhaust at ground level. Do not allow containers to stand open. Do not inhale substance.

Avoid contact with skin and eyes.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Do not weld. Use grounding equipment. Use only spark proof tools. Beware of reignition.



Revision date: according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: (REACH)



2,3',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-086S

Version 2 / Page 4 of 9

09.07.2011

30.01.2011

28.07.2010

Date of print:

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place. Keep away from sources of ignition and heat. Qualified materials: steel, stainless steel, aluminium Do not store together with combustible or self-igniting materials or any highly flammable solids. Hints on joint storage Keep away from food, drink and animal feeding stuffs. 3 = Flammable liquids Storage class: 7.3 Specific end use(s)

No data available

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

| CAS No.  | Chemical name | Туре                   | Limit value      |
|----------|---------------|------------------------|------------------|
| 110-54-3 | n-Hexane      | Great Britain: WEL-TWA | 72 mg/m³; 20 ppm |
|          |               | Europe, IOELV: TWA     | 72 mg/m³; 20 ppm |

#### 8.2 Exposure controls

Execute works under fume hood. Do not inhale substance. The substance should only be handled in closed apparatus or systems. In case of spill or release: Use local exhaust.

#### **Occupational exposure controls**

| Respiratory protection:   | Respiratory protection must be worn whenever the WEL levels have been exceeded.<br>Use filter type A (= against vapours of organic substances), identification colour brown,<br>according to EN 141.   |
|---------------------------|--|
| Hand protection:          | Protective gloves according to EN 374.<br>Glove material: Nitrile rubber (0,35 mm) or fluoro rubber (0,4 mm).<br>Unsuitable materials: natural rubber, butyl caoutchouc (butyl rubber), PVC.<br>Breakthrough time: > 480 min.<br>Observe glove manufacturer's instructions concerning penetrability and breakthrough time. |
| Eye protection:           | Tightly sealed safety glasses according to EN 166.   |
| Body protection:          | Wear suitable protective clothing.<br>In case of handling larger quantities: flame-retardant protective clothing, antistatic   |
| General protection and hy | giene measures:  |
|                           | Take off immediately all contaminated clothing.  |
|                           | Wash hands before breaks and after work.   |
|                           | When using do not eat, drink or smoke.   |
|                           | Have eye wash bottle or eye rinse ready at work place.   |

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

| Physical state:                     | liquid            |
|-------------------------------------|-------------------|
| Colour                              | colourless        |
| Odour:                              | weak like benzine |
| Boiling temperature / boiling range | 68,7 °C           |
| Flash point / flash point range:    | -26 °C            |
| Ignition temperature                | 230 °C            |

printed by LGC Standards



according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: (REACH)

 Date of print:
 09.07.2011

 Revision date:
 30.01.2011

 Date of first version:
 28.07.2010

2,3',5-Tribromobiphenyl 100 µg/mL in Hexane Material number U-RBF-086S Version 2 / Page 5 of 9

| Explosion limits:                       | LEL (Lower Explosion Limit): 1,00 Vol-% (n-Hexane)                              |
|---|---|
|   | UEL (Upper Explosive Limit): 8,90 Vol-% (n-Hexane)                              |
| Vapour pressure:                        | at 20 °C: 160 hPa (n-Hexane)  |
|   | at 50 °C: 540 hPa (n-Hexane)  |
| Density:                                | at 20 °C: approx. 0,66 g/mL   |
| Water solubility:                       | at 20 °C: 50 mg/L (n-Hexane)  |
| Partition coefficient n-octanol /water: | 4,11 log P(o/w) (n-Hexane)  |
|   | An appreciable bioaccumulation potential is to be expected (log $P(o/w) > 3$ ). |

#### 9.2 Other information

Information about n-Hexane: Molecular weight: 86,18 g/mol Relative vapour density at 20 °C (air=1): 2,98 Concentration of the saturated vapour (20°C): 566 g/m<sup>3</sup>

## **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

No data available

#### **10.2 Chemical stability**

Attacks many plastics and rubbers.

#### **10.3 Possibility of hazardous reactions**

No data available

#### 10.4 Conditions to avoid

Highly flammable. Liquid evaporates very quickly. Keep away from heat sources, sparks and open flames. Vapours form potentially explosive mixtures with air. Heavier than air, they proceed at floor level and may backflash over great distances when ignited. Ignition by hot surfaces, sparks and open flames.

#### 10.5 Incompatible materials

strong oxidizing agents (Ignition hazard/Danger of explosion!)

#### **10.6 Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide and carbon dioxide, traces of incompletely burned carbon compounds.

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

| ia, |
|-----|
|     |
| i   |



Revision date: 30.01.2011 according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: 28.07.2010 (REACH)

# 2,3',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-086S

Version 2 / Page 6 of 9

09 07 2011

Date of print:

| After swallowing:   | Harmful: may cause lung damage if swallowed.<br>When swallowed and vomited immediately, aspiration into the lungs may occur resulting in chemical pneumonia or suffocation. |  |
|---|---|--|
| In case of skin contact:  | Irritant. Danger of cutaneous absorption.   |  |
| After eye contact:  | Irritant. Risk of corneal clouding.   |  |
| carcinogenic, germ cell mutagen and reproduction effects<br>Repr. Cat. 3. Rossible risk of impaired fertility |   |  |

Repr. Cat. 3 - Possible risk of impaired tertility.

#### General remarks

Information about n-Hexane: Chromosomal aberrations mammalian cells (in-vitro): negative. Bacterial mutagenicity: Salmonella typhimurium: negative.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Information about n-Hexane: Daphnia toxicity: EC50 Daphnia magna: 2,1 mg/L/48h. Fish toxicity: LC50 Pimephales promelas: 2,5 mg/L/96h. 2 = hazardous to water

Water Hazard Class:

#### 12.2. Persistence and degradability

Further details:

Information about n-Hexane: Substance floats on the water surface. Potentially explosive mixtures with air may form above water surface. Bioconcentration factor (BCF): 242 - 453

#### 12.3 Bioaccumulative potential

Partition coefficient n-octanol /water:

4,11 log P(o/w) (n-Hexane)

An appreciable bioaccumulation potential is to be expected (log P(o/w) > 3).

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

No data available

#### 12.6 Other adverse effects

General information:

Do not allow to enter into ground-water, surface water or drains. In case of spills of large quantities: Danger to drinking water.

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

#### Product

- Waste key number
- laboratory chemicals consisting of or containing dangerous substances including 16 05 06\* = mixtures of laboratory chemicals.

\* = Evidence for disposal must be provided.



according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: 28.07.2010 (REACH)

#### 2,3',5-Tribromobiphenyl 100 µg/mL in Hexane Version 2 / Page 7 of 9

Material number U-RBF-086S

Recommendation:

Incinerate as hazardous waste according to applicable local, state, and federal regulations. Discharge into the environment must be avoided.

#### Contaminated packaging

Waste key number 15 01 07 = Glass packaging. Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

# **SECTION 14: Transport information**

#### 14.1 UN number

ADR/RID, IMDG, IATA: 1208

#### 14.2 UN proper shipping name

ADR/RID: UN 1208, HEXANES, solution IMDG, IATA: HEXANE, solution

#### 14.3 Transport hazard class(es)

| ADR/RID: | Class 3, Code: F1 |
|----------|-------------------|
| IMDG:    | Class 3, Code -   |
| IATA:    | Class 3           |

Ш

Yes

#### 14.4 Packing group

ADR/RID, IMDG, IATA:

#### 14.5 Environmental hazards

Marine Pollutant

#### 14.6 Special precautions for user

#### Land transport (ADR/RID)

| Warning board:                          | ADR/RID: Kemmler-number 33, UN number 1208 |
|---|--|
| Hazard label                            | 3  |
| Limited quantities                      | 1 L  |
| EQ                                      | E2   |
| Contaminated packaging: Instructions    | P001 IBC02 R001                            |
| Special provisions for packing together | MP19                                       |
| Portable tanks: Instructions            | T4   |
| Portable tanks: Special provisions      | TP1  |
| Tank coding                             | LGBF                                       |
| Tunnel restriction code:                | D/E  |





according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: 2 (REACH)

# 2,3',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-086S

Version 2 / Page 8 of 9

#### Sea transport (IMDG)

| EmS:                                 | F-E, S-D   |                   |
|--------------------------------------|--|-------------------|
| Special provisions                   | -  | JHL               |
| Limited quantities                   | 1L   |                   |
| EQ                                   | E2   |                   |
| Contaminated packaging: Instructions | P001   | 3                 |
| Contaminated packaging: Provisions   | -  | ×                 |
| IBC: Instructions                    | IBC02  |                   |
| IBC: Provisions                      | -  |                   |
| Tank instructions: IMO               | -  |                   |
| Tank instructions: UN                | T4   |                   |
| Tank instructions Provisions         | TP1  | $\mathbf{\nabla}$ |
| Stowage and segregation              | Category E.  |                   |
| Properties and observations          | Colourless, volatile liquids with a faint odour. Explosive limits: 1.1% to 7.5%. n-HEXANE: flashpoint -22°C c.c. boiling point 69°C. |                   |
|                                      | Immiscible with water. Slightly irritating to skin, eyes and mucous membranes.   |                   |
| Air transport (IATA)                 |  |                   |
| Hazard                               | Flamm. liquid  |                   |
| EQ                                   | E2   | JHL I             |
| Passenger Ltd.Qty.:                  | Pack.Instr. Y341 - Max.Qty. 1 L  |                   |

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pack.Instr. 353 - Max.Qty. 5 L

Pack.Instr. 364 - Max.Qty. 60 L

No data available

3H

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations - Great Britain

Hazchem-Code:

Passenger:

Cargo: ERG

### National regulations - Germany

Storage class: 3 = Flammable liquids

3YE

Water Hazard Class: 2 = hazardous to water

Informations on working limitations:

Information about n-Hexane: Pregnancy risk group C.


- There is no risk of damage to the embryo when WEL values are observed.
- Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

### National regulations - USA

| •                     |
|-----------------------|
| Hazard rating systems |
| 2 0                   |

NFPA Hazard Rating: Health: 2 (Moderate) Fire: 3 (Serious) Reactivity: 0 (Minimal) HMIS Version III Rating: Health: 2 (Moderate) Flammability: 3 (Serious) Physical Hazard: 0 (Minimal) Personal Protection: X = Consult your supervisor





Revision date: according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: 28.07.2010 (REACH)



2,3',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-086S

Version 2 / Page 9 of 9

09.07.2011

30.01.2011

Date of print:

#### **15.2 Chemical Safety Assessment**

No data available

# **SECTION 16: Other information**

#### **Further remarks**

| R phrase(s):      | R 11 = Highly flammable.   |
|-------------------|--|
|                   | R 22 = Harmful if swallowed.   |
|                   | R 33 = Danger of cumulative effects.   |
|                   | R 36/37/38 = Irritating to eyes, respiratory system and skin.  |
|                   | R 38 = Irritating to skin.   |
|                   | R 48/20 = Harmful: danger of serious damage to health by prolonged exposure through inhalation.            |
|                   | R 50/53 = Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
|                   | R 51/53 = Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic<br>environment.   |
|                   | R 62 = Possible risk of impaired fertility.  |
|                   | R 65 = Harmful: may cause lung damage if swallowed.  |
|                   | R 67 = Vapours may cause drowsiness and dizziness.   |
| Reason of change: | Changes in section 14: ADR 2011, IATA 2011, General revision   |
| Literature:       | ICSC 0279  |
| _                 |  |

#### Group that issues data sheet

Contact person: see chapter 1, department responsible for information.

The information in this safety data sheet (SDS) has been prepared with due care and is true and accurate to the best of our knowledge. The user must determine the suitability of the information for its particular purpose, ensure compliance with existing laws and regulations, and be aware that other or additional safety or performance considerations may arise when using, handling and/or storing the material.

The information in this SDS does not purport to be all inclusive or a guarantee as to the properties of the material supplied, and should be used only as a guide. LGC makes no warranties or representations as to the accuracy and completeness of the information contained herein. LGC shall not be held responsible for the suitability of this information for the user's intended purposes or the consequences of such use, and shall not be liable for any damage or loss, howsoever arising, direct or otherwise.