

according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version:

2,2',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-085S

Date of print:

Revision date:

30.01.2011

23.07.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 2,2',5-Tribromobiphenyl 100 µg/mL in Hexane

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use specific analysis

1.3 Details of the supplier of the safety data sheet

LGC Standards GmbH Company name:

Mercatorstr. 51 Street/POB-No.: D-46485 Wesel State/city/postal code:

World Wide Web: www.lgcstandards.com Email: de@lgcstandards.com Telephone: +49 (0)281-98 87-0 +49 (0)281-98 87-199 Telefax:

Dept. responsible for information:

Telephone: +49 (0)281-98 87-0, Email: de@lgcstandards.com

1.4 Emergency telephone number

Telephone: +49 (0)281-98 87-0 Only available during office hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Repr. Cat. 3; R62 Possible risk of impaired fertility.

F; R11 Highly flammable.

Xn; R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful: may cause lung damage if swallowed. Xn; R65

Xi; R38 Irritating to skin.

R67 Vapours may cause drowsiness and dizziness.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. N; R51-53

2.2 Label elements

Labelling (67/548/EEC or 1999/45/EC)







highly flammable harmful

dangerous for the environment

R phrase(s): R 11 Highly flammable.

R 38

Irritating to skin. R 48/20 Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R 62 Possible risk of impaired fertility.

R 65 Harmful: may cause lung damage if swallowed. R 67 Vapours may cause drowsiness and dizziness.



according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: 23.07.2010

Date of print: Revision date: 30.01.2011

Excellence through measurement

2,2',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-085S

S phrase(s):	S (2)	Keep out of the reach of children.
	S 9	Keep container in a well-ventilated place.
	S 16	Keep away from sources of ignition - No smoking.
	S 29	Do not empty into drains.
	S 33	Take precautionary measures against static discharge.
	S 36/37	Wear suitable protective clothing and gloves.
	S 61	Avoid release to the environment. Refer to special instructions / safety data sheet.
	S 62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Text for labelling Contains n-Hexane.

2.3 Other hazards

No risks worthy of mention.

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Hazardous ingredients:

Ingredient	Chemical name	Content	Classification
EINECS - CAS 59080-34-1	2,2',5-PBB	< 0,1 %	EU: N; R50-53. R33. Xn; R22. Xi; R36/37/38. CLP: Acute Tox. 4; H302. Skin Irrit. 2; H315. Eye Irrit. 2; H319. STOT SE 3; H335. STOT RE 2; H373. Aquatic Acute 1; H400. Aquatic Chronic 1; H410.
EINECS 203-777-6 CAS 110-54-3	n-Hexane	>= 99,9 %	EÚ: F; R11. N; R51-53. R67. Repr. Cat. 3; R62. Xi; R38. Xn; R48/20. Xn; R65. CLP: Flam. Liq. 2; H225. Skin Irrit. 2; H315. Repr. 2; H361f. STOT SE 3; H336. STOT RE 2; H373. Asp. Tox. 1; H304. Aquatic Chronic 2; H411.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation: Move victim to fresh air. If the casualty has difficulty breathing, call a doctor immediately.

If breathing becomes irregular or ceases, apply mouth-to-mouth resuscitation or artificial

respiration immediately, where required supply oxygen.

Take off immediately all contaminated clothing. In case of skin contact:

After contact with skin, wash immediately with soap and plenty of water.

In case of skin irritation, consult a physician.

With eyelids open, wash out eyes for several minutes under flowing water. In case of troubles After eye contact:

or persistent symptoms, consult an opthalmologist.

After swallowing: Rinse mouth thoroughly with water.

> Caution if victim vomits: Risk of aspiration! Immediately get medical attention. Keep airway open. Give activated carbon (20 - 40 g in a suspension of 10%).

Do not give fatty oils and milk.

4.2 Most important symptoms and effects, both acute and delayed

No data available

4.3 Indication of any immediate medical attention and special treatment needed

No special measures are required.



according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: 23.07.2010 (REACH)

2,2',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-085S Version 2 / Page 3 of 9

Date of print:

Revision date:

30.01.2011

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Extinguishing powder, foam, carbon dioxide.

In case of greater fires: Foam or water fog.

Extinguishing media which must not be used for safety reasons:

High power water jet

5.2 Special hazards arising from the substance or mixture

Highly flammable. Explosive mixtures with air may even form at room temperature.

Concentrated vapours are heavier than air. Beware of reignition.

In case of fire may be liberated: Carbon monoxide and carbon dioxide, traces of incompletely burned carbon compounds.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained breathing apparatus. Wear full protective gear.

Additional information:

Cool endangered containers with water spray and, if possible, remove from danger zone. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Plug leak if safely possible.

Avoid contact with the substance. Wear suitable protective clothing.

Do not breathe vapour/aerosol. Provide adequate ventilation.

In case of spills of large quantities: Use appropriate respiratory protection.

6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains. Danger of explosion! In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Take up with non-flammable, liquid binding material (e.g. sand/earth/diatomaceous

earth/vermiculit) and perform disposal according to instructions. Thoroughly clean surrounding

area.

In case of spills of large quantities: Dam spills and pump to remove. Contact expert.

Additional information: Beware of reignition. Use only spark proof tools.

6.4 Reference to other sections

not required

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling Provide adequate ventilation, and local exhaust as needed.

Execute works under fume hood. Provide room air exhaust at ground level.

Do not allow containers to stand open. Do not inhale substance.

Avoid contact with skin and eyes.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Do not weld. Use grounding equipment. Use only spark proof tools. Beware of reignition.



according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version:

2,2',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-085S Version 2 / Page 4 of 9

Date of print:

Revision date:

30.01.2011

23.07.2010

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.

Keep away from sources of ignition and heat.

Qualified materials: steel, stainless steel, aluminium

Hints on joint storage Do not store together with combustible or self-igniting materials or any highly flammable solids.

Keep away from food, drink and animal feeding stuffs.

Storage class: 3 = Flammable liquids

7.3 Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

CAS No.	Chemical name	Туре	Limit value
110-54-3	n-Hexane	Great Britain: WEL-TWA	72 mg/m³; 20 ppm
		Europe, IOELV: TWA	72 mg/m³; 20 ppm

8.2 Exposure controls

Execute works under fume hood. Do not inhale substance.

The substance should only be handled in closed apparatus or systems.

In case of spill or release: Use local exhaust.

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded.

Use filter type A (= against vapours of organic substances), identification colour brown,

according to EN 141.

Hand protection: Protective gloves according to EN 374.

Glove material: Nitrile rubber (0,35 mm) or fluoro rubber (0,4 mm).

Unsuitable materials: natural rubber, butyl caoutchouc (butyl rubber), PVC.

Breakthrough time: > 480 min.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed safety glasses according to EN 166.

Body protection: Wear suitable protective clothing.

In case of handling larger quantities: flame-retardant protective clothing, antistatic

General protection and hygiene measures:

Take off immediately all contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink or smoke.

Have eye wash bottle or eye rinse ready at work place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: liquid
Colour colourless

Odour: weak like benzine

Boiling temperature / boiling range $68.7\,^{\circ}\text{C}$ Flash point / flash point range: $-26\,^{\circ}\text{C}$ Ignition temperature $230\,^{\circ}\text{C}$



Excellence through measurement

EU SAFETY DATA SHEET

Revision date: according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version:

2,2',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-085S

Date of print:

30.01.2011

23.07.2010

LEL (Lower Explosion Limit): 1,00 Vol-% (n-Hexane) Explosion limits:

UEL (Upper Explosive Limit): 8,90 Vol-% (n-Hexane)

at 20 °C: 160 hPa (n-Hexane) Vapour pressure:

at 50 °C: 540 hPa (n-Hexane)

Density: at 20 °C: approx. 0,66 g/mL at 20 °C: 50 mg/L (n-Hexane) Water solubility: Partition coefficient n-octanol /water: 4,11 log P(o/w) (n-Hexane)

An appreciable bioaccumulation potential is to be expected (log P(o/w) > 3).

9.2 Other information

Information about n-Hexane: Molecular weight: 86,18 g/mol

Relative vapour density at 20 °C (air=1): 2,98

Concentration of the saturated vapour (20°C): 566 g/m³

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Attacks many plastics and rubbers.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Highly flammable. Liquid evaporates very quickly.

Keep away from heat sources, sparks and open flames.

Vapours form potentially explosive mixtures with air. Heavier than air, they proceed at floor level and may backflash over great distances when ignited. Ignition by hot surfaces, sparks and open flames.

10.5 Incompatible materials

strong oxidizing agents (Ignition hazard/Danger of explosion!)

10.6 Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide and carbon dioxide, traces of incompletely burned carbon compounds.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD50 Rat, oral: 5000 mg/kg (n-Hexane) LC50 Rat, inhalative: 48000 ppm/4h (n-Hexane) LD50 Rat, dermal: 3000 mg/kg (n-Hexane)

After inhalation: Vapours may cause drowsiness and dizziness.

Danger of serious damage to health by prolonged exposure.

Other symptoms: Mucous membrane irritation, headache, fatigue, dizziness, amyosthenia,

dizziness, unconsciousness, apnea, narcosis, CNS disorders, muscle paralysis.



Excellence through measurement

EU SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Revision date:

Date of first version:

2,2',5-Tribromobiphenyl 100 µg/mL in Hexane

Date of print:

30.01.2011

23.07.2010

Material number U-RBF-085S

After swallowing: Harmful: may cause lung damage if swallowed.

When swallowed and vomited immediately, aspiration into the lungs may occur resulting in

chemical pneumonia or suffocation.

In case of skin contact: Irritant. Danger of cutaneous absorption.

After eye contact: Irritant. Risk of corneal clouding.

carcinogenic, germ cell mutagen and reproduction effects

Repr. Cat. 3 - Possible risk of impaired fertility.

General remarks

Information about n-Hexane:

Chromosomal aberrations mammalian cells (in-vitro): negative. Bacterial mutagenicity: Salmonella typhimurium: negative.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information about n-Hexane:

Daphnia toxicity:

EC50 Daphnia magna: 2,1 mg/L/48h.

Fish toxicity:

LC50 Pimephales promelas: 2,5 mg/L/96h.

Water Hazard Class: 2 = hazardous to water

12.2. Persistence and degradability

Further details: Information about n-Hexane:

Substance floats on the water surface.

Potentially explosive mixtures with air may form above water surface.

Bioconcentration factor (BCF): 242 - 453

12.3 Bioaccumulative potential

Partition coefficient n-octanol /water:

4,11 log P(o/w) (n-Hexane)

An appreciable bioaccumulation potential is to be expected (log P(o/w) > 3).

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

In case of spills of large quantities: Danger to drinking water.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number 16 05 06* = laboratory chemicals consisting of or containing dangerous substances including

mixtures of laboratory chemicals.

* = Evidence for disposal must be provided.



according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version:

2,2',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-085S Version 2 / Page 7 of 9

Date of print:

Revision date:

30.01.2011

23.07.2010

Recommendation: Incinerate as hazardous waste according to applicable local, state, and federal regulations.

Discharge into the environment must be avoided.

Contaminated packaging

Waste key number 15 01 07 = Glass packaging.

Recommendation: Dispose of waste according to applicable legislation.

Handle contaminated packages in the same way as the substance itself.

Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA: 1208

14.2 UN proper shipping name

ADR/RID: UN 1208, HEXANES, solution

IMDG, IATA: HEXANE, solution

14.3 Transport hazard class(es)

ADR/RID: Class 3, Code: F1 Class 3, Code -

IATA: Class 3

14.4 Packing group

ADR/RID, IMDG, IATA:

14.5 Environmental hazards

Marine Pollutant Yes

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: ADR/RID: Kemmler-number 33, UN number 1208

Hazard label 3
Limited quantities 1 L
EQ E2

Contaminated packaging: Instructions P001 IBC02 R001

Special provisions for packing together MP19
Portable tanks: Instructions T4
Portable tanks: Special provisions TP1
Tank coding LGBF
Tunnel restriction code: D/E







Excellence through measurement

EU SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version:

2,2',5-Tribromobiphenyl 100 μg/mL in Hexane

Material number U-RBF-085S Version 2 / Page 8 of 9

Date of print:

Revision date:

30.01.2011

23.07.2010

Sea transport (IMDG)

EmS: F-E, S-D

Special provisions Limited quantities 1 L
EQ E2
Contaminated packaging: Instructions P001
Contaminated packaging: Provisions IBC: Instructions IBC02

Tank instructions: IMO Tank instructions: UN T4
Tank instructions Provisions TP1

Stowage and segregation Category E.

Properties and observations Colourless, volatile liquids with a faint odour. Explosive limits: 1.1%

to 7.5%. n-HEXANE: flashpoint -22°C c.c. boiling point 69°C. Immiscible with water. Slightly irritating to skin, eyes and mucous

membranes.

Air transport (IATA)

IBC: Provisions

Hazard Flamm. liquid

EQ E2

Passenger Ltd.Qty.: Pack.Instr. Y341 - Max.Qty. 1 L
Passenger: Pack.Instr. 353 - Max.Qty. 5 L
Cargo: Pack.Instr. 364 - Max.Qty. 60 L

ERG 3H



14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code: 3YE

National regulations - Germany

Storage class: 3 = Flammable liquids
Water Hazard Class: 2 = hazardous to water

Informations on working limitations:

Information about n-Hexane: Pregnancy risk group C.

There is no risk of damage to the embryo when WEL values are observed.

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

National regulations - USA


Hazard rating systems



NFPA Hazard Rating: Health: 2 (Moderate) Fire: 3 (Serious) Reactivity: 0 (Minimal)

HMIS Version III Rating: Health: 2 (Moderate) Flammability: 3 (Serious) Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor





according to Regulation (EC) No. 1907/2006 and Regulation (EU) No 453/2010 Date of first version: 23.07.2010 (REACH)

2,2',5-Tribromobiphenyl 100 µg/mL in Hexane

Material number U-RBF-085S Version 2 / Page 9 of 9

Date of print:

Revision date:

30.01.2011

15.2 Chemical Safety Assessment

No data available

SECTION 16: Other information

Further remarks

R phrase(s): R 11 = Highly flammable.

R 22 = Harmful if swallowed.

R 33 = Danger of cumulative effects.

R 36/37/38 = Irritating to eyes, respiratory system and skin.

R 38 = Irritating to skin.

R 48/20 = Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R 50/53 = Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R 51/53 = Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R 62 = Possible risk of impaired fertility.

R 65 = Harmful: may cause lung damage if swallowed. R 67 = Vapours may cause drowsiness and dizziness.

Reason of change: Changes in section 14: ADR 2011, IATA 2011, General revision

Literature: ICSC 0279

Group that issues data sheet

Contact person: see chapter 1, department responsible for information.

The information in this safety data sheet (SDS) has been prepared with due care and is true and accurate to the best of our knowledge. The user must determine the suitability of the information for its particular purpose, ensure compliance with existing laws and regulations, and be aware that other or additional safety or performance considerations may arise when using, handling and/or storing the material.

The information in this SDS does not purport to be all inclusive or a guarantee as to the properties of the material supplied, and should be used only as a guide. LGC makes no warranties or representations as to the accuracy and completeness of the information contained herein. LGC shall not be held responsible for the suitability of this information for the user's intended purposes or the consequences of such use, and shall not be liable for any damage or loss, howsoever arising, direct or otherwise.